

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	75520	"396".clas.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/06/22 10:49
L2	24309	"396".clas. and shutter	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/06/22 10:49
L3	370	"396".clas. and shutter with pattern	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/06/22 10:49
L4	34	"396".clas. and shutter with pattern with element	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/06/22 10:51
L5	2250	"396".clas. and shutter near4 element	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/06/22 10:52
L6	11	"396".clas. and shutter near4 element with pattern	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/06/22 10:56
L7	405	382/313.ccls.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/06/22 10:57
L8	14	382/313.ccls. and shutter	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/06/22 10:57


[Home](#) | [Login](#) | [Logout](#) | [Access Information](#) | [Alerts](#) |

Welcome United States Patent and Trademark Office

Search Results

BROWSE

SEARCH

IEEE XPLORE GUIDE

Results for "(((shutter)&lt;in&gt;metadata)&lt;and&gt;(camera&lt;in&gt;metadata))"

Your search matched 79 of 354 documents.

A maximum of 100 results are displayed, 25 to a page, sorted by Relevance in Descending order.

» [View Session History](#)» [New Search](#)» [Key](#)

IEEE JNL IEEE Journal or Magazine

IEE JNL IEE Journal or Magazine

IEEE CNF IEEE Conference Proceeding

IEE CNF IEE Conference Proceeding

IEEE STD IEEE Standard

## Modify Search

☐ Check to search only within this results setDisplay Format: ☒ Citation ☐ Citation & Abstract

Select Article Information

View: 1-25 | [26-](#)

- |                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <input type="checkbox"/> | <p><b>1. An open and shut case [computer graphics]</b><br/> Glassner, A.;<br/> Computer Graphics and Applications, IEEE<br/> Volume 19, Issue 3, May-June 1999 Page(s):82 - 92<br/> <a href="#">AbstractPlus</a>   Full Text: <a href="#">PDF</a>(8600 KB) IEEE JNL</p>                                                                                                                                                                                                                                                                                                   |
| <input type="checkbox"/> | <p><b>2. Frame-rate displacement measurement system utilizing an ultra-high-speed shut an optical correlator</b><br/> Toyoda, H.; Kobayashi, Y.; Mukohzaka, N.; Yoshida, N.; Hara, T.; Ohno, T.;<br/> Instrumentation and Measurement, IEEE Transactions on<br/> Volume 44, Issue 3, June 1995 Page(s):755 - 758<br/> <a href="#">AbstractPlus</a>   Full Text: <a href="#">PDF</a>(340 KB) IEEE JNL</p>                                                                                                                                                                  |
| <input type="checkbox"/> | <p><b>3. Single camera three-dimensional endoscope system using a ferroelectric liquid c</b><br/> Lester, G.A.; Watts, J.; Wilmington, D.;<br/> Science, Measurement and Technology, IEE Proceedings-<br/> Volume 145, Issue 2, March 1998 Page(s):49 - 51<br/> <a href="#">AbstractPlus</a>   Full Text: <a href="#">PDF</a>(308 KB) IEE JNL</p>                                                                                                                                                                                                                         |
| <input type="checkbox"/> | <p><b>4. Real-time displacement measurement using a pattern correlation system incorpc high-speed shutter camera and parallel aligned nematic liquid crystal spatial ligh (PAL-SLMs)</b><br/> Toyoda, H.; Kobayashi, Y.; Mukohzaka, N.; Yoshida, N.; Hara, T.; Ohno, T.;<br/> Instrumentation and Measurement Technology Conference, 1994. IMTC/94. Conferenc<br/> 10th Anniversary. Advanced Technologies in I &amp; M., 1994 IEEE<br/> 10-12 May 1994 Page(s):1345 - 1348 vol.3<br/> <a href="#">AbstractPlus</a>   Full Text: <a href="#">PDF</a>(248 KB) IEEE CNF</p> |
| <input type="checkbox"/> | <p><b>5. Analysis for improvement of simultaneity of shuttering in an ultra high-speed fra</b><br/> Ito, Y.; Kato, Y.; Kagata, M.; Tomioka, S.; Enoto, T.;<br/> Magnetics, IEEE Transactions on<br/> Volume 36, Issue 4, July 2000 Page(s):1774 - 1778<br/> <a href="#">AbstractPlus</a>   <a href="#">References</a>   Full Text: <a href="#">PDF</a>(128 KB) IEEE JNL</p>                                                                                                                                                                                               |
| <input type="checkbox"/> | <p><b>6. 3-dimensional personal computer system</b><br/> Iwasaki, K.; Karibe, I.; Nakai, K.; Ueno, A.;<br/> Consumer Electronics, IEEE Transactions on</p>                                                                                                                                                                                                                                                                                                                                                                                                                |